

# LEAD FLASHING THEORY WEIGHTS

BS EN 12588:2006 (+/- 5% Tolerance)

Document No: FRWPB001

Version No:001

Uncontrolled When Printed



specified • sustainable • delivered

		CODE 3		CODE 4		CODE 5		CODE 6		CODE 7		CODE 8	
Nominal Thickness		1.32mm		1.80mm		2.24mm		2.65mm		3.15mm		3.55mm	
STANDARD WIDTHS		3m	6m	3m	6m	3m	6m	3m	6m	3m	6m	3m	6m
MM	Nearest Imperial	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg
150	6"	7.0	13.5	9.0	18.5	11.5	23.0	13.5	27.0	16.0	32.0	18.0	36.0
180	7"	8.0	16.0	11.0	22.0	14.0	27.5	16.5	32.0	19.5	38.5	22.0	43.5
210	8"	9.0	19.0	13.0	26.0	16.0	32.0	19.0	38.0	22.5	45.0	25.5	51.0
225	9"	10.5	20.5	14.0	28.0	17.0	34.0	20.5	41.0	24.0	48.0	27.0	54.5
240	9½"	11.0	21.5	14.5	29.0	18.0	36.5	22.0	43.5	26.0	51.5	29.0	58.0
300	12"	13.0	27.0	18.5	37.0	23.0	46.0	27.0	54.0	32.0	64.5	36.0	72.5
360	14"	16.0	32.5	22.0	44.0	27.5	55.0	32.5	65.0	38.5	77.0	43.5	87.0
390	15"	18.0	35.0	24.0	48.0	30.0	59.5	35.0	70.5	42.0	84.0	47.0	94.0
420	16"	19.0	38.0	26.0	51.5	32.0	64.0	38.0	76.0	45.0	90.0	51.0	101.5
450	18"	20.0	40.5	28.0	55.0	34.5	69.0	41.0	81.5	48.0	96.5	54.5	109.0
510	20"	23.0	46.0	31.0	62.5	39.0	78.0	46.0	92.0	55.0	109.5	61.5	123.0
600	24"	27.0	54.0	37.0	73.5	46.0	91.5	54.0	108.5	64.5	128.5	72.5	145.0
760	30"	34.0	67.5	47.0	93.0	58.0	116.0	69.0	137.0	81.0	163.0	92.0	184.0
800	32"	36.0	72.0	49.0	98.0	61.0	122.0	72.0	144.0	86.0	171.0	97.0	193.0
900	36"	40.0	81.0	55.0	110.0	69.0	137.0	81.5	162.5	96.5	193.0	109.0	217.0
914	36½"	41.0	82.0	56.0	112.0	70.0	139.5	82.5	165.0	98.0	196.0	110.5	221.0
1,000	39"	45.0	90.0	61.0	122.5	76.0	152.5	90.0	180.0	107.0	214.0	121.0	242.0
1200	4'-0"	54.0	108.0	73.5	147.0	91.5	183.0	108.5	217.0	128.5	257.0	145.0	290.0
1,400	56"	63.0	126.0	86.0	171.5	107.0	213.5	126.5	253.0	150.0	300.0	169.0	338.0
<b>Weight per m<sup>2</sup></b>		<b>15.0 kg</b>		<b>20.41 kg</b>		<b>25.40 kg</b>		<b>30.10 kg</b>		<b>35.72 kg</b>		<b>40.26 kg</b>	

These rolls are commonly ordered sizes and are an example of our range, any size from 100mm to 1400mm wide can be prepared to order.

To calculate the approximate weight of a piece of Rolled Lead Sheet, multiply the length in metres by the width in metres and then multiply by the Code weight in kg/m<sup>2</sup> shown in the table above.



T: 01543 495250 • F: 01543 495251 • E: enquiries@centralmilledlead.com

Central Milled Lead Ltd • The Lead Mill • Rolling Mill Road  
Norton Canes • Cannock • Staffordshire • WS11 9UH

Company registered in England & Wales No. 04291304 VAT Registration No: 855 0715 24

www.centralmilledlead.com



T: 01543 495250 • F: 01543 495251 • E: [enquiries@centralmilledlead.com](mailto:enquiries@centralmilledlead.com)

Central Milled Lead Ltd • The Lead Mill • Rolling Mill Road  
Norton Canes • Cannock • Staffordshire • WS11 9UH

Company registered in England & Wales No. 04291304 VAT Registration No: 855 0715 24

[www.centralmilledlead.com](http://www.centralmilledlead.com)